


CODE	COLOUR
1	Nero/ Black
2	Rosso/Red
3	Verde/Green
4	Giallo/Yellow
5	Blu/Blue
6	Marrone/Brown
7	Grigio/Grey
8	Viola/Violet
9	Arancione/Orange

CODE	MATERIAL	UL94	GWT	RTI Elec	Approval
CT1004L	Nylon 66	V2	—	105° C	UL
CT1004LH	Nylon 66	V2	750 °C flame	130 °C	UL
CT1004LV	Nylon 46	V2	—	150 °C	—
CT1004LV0	Nylon 6/66	V0	—	140 °C	UL
CT1004LZ	Nylon 66	V0	750 °C flame	65 °C	UL
CT1004LV0NF	Nylon 66	V0	750 °C flame	140 °C	UL

Tutti i codici possono essere seguiti da un carattere numerico indicante il colore
 All the Cat. Nos. may be followed by one alphanumeric character indicating the color

INDEX	DESCRIPTION	DATE
05	UPDATED MATERIAL CHARACTERISTICS	27 MAG 2013
04	ADDED CODES FOR COLOURS	18 OTT 2012
03	MODIFIED FOR 2,8 LOW INSER. FORCE	23 NOV 2011

NAME CT1004L CONNECTOR FEMALE TERMINAL 2,8mm LOW INSERTION FORCE		Questo disegno è un documento a distribuito in forma controllata, a termine di legge Mikropla si riserva le sue proprietà con diritto di uso e riproduzione. È vietato il ricambio ed approssimamenti, contattare l'ufficio tecnico per la versione più recente. This drawing is a controlled document. It is subject to change and the controlling engineering organization should be contacted for the latest revision.	
TOLERANCES UNLESS OTHERWISE SPECIFIED : 0 PLC ± 0.5 1 PLC ± 0.3 2 PLC ± 0.1 ANGLES ± 2°		MATERIAL : SEE TABLE WEIGHT : — FINISH : —	
 mikropla MIKROPLA s.r.l. Via Giovanni Pascoli, 36 - 60044 FABRIANO (AN) - IT		DWN. : C.S. DATE : 26-GIU-2009 CHK. : G.C. DATE : 27 MAG 2013 REV. : 05	
		DIMENSIONS : mm SCALE : 4,1 SIZE : A4 SHEET 1 OF 1	