

# SPEEDY 40 / SPEEDY 40 H

## THE HIGH PERFORMANCE PROCESSING CENTER FOR CABLES



### FEATURES

- Ink-jet printing with multiple colours (single- or doublesided) is available. The positioning of the print heads close to the cutting blades avoids cable waste
- A slitting unit for intermediate stripping and for long stripping length (at the beginning and the end of cable) is available
- The Speedy 40 is designed to also process larger cables with high copper content or cross sections up to 400 mm<sup>2</sup>
- Optional software modules available, e.g. for multi-step / multi-layer stripping

For cables up to  $\varnothing$  40 mm with gentle cable transport trough use of transport belts. The optional hydraulic cutting unit, for example Speedy 40 H, is characterised by an unprecedented power reserve for hard-to-process cables with a high copper content and a cross-section of up to 400 mm<sup>2</sup>.

## TECHNICAL DATA

Performance	Speedy 40	Speedy 40 H
Cable diameter	Cutting and stripping $\varnothing$ 3 up to $\varnothing$ 40 mm	Cutting and stripping $\varnothing$ 3 up to $\varnothing$ 40 mm
Cable cross section	up to 240 mm <sup>2</sup>	up to 400 mm <sup>2</sup>
Cable length	220 mm up to 1000 m	220 mm up to 1000 m
Tolerance in length	Precision in repetition (by length more than 2 m) better than $\pm$ 0,2%	Precision in repetition (by length more than 2 m) better than $\pm$ 0,2%
Stripping length	Beginning and ending ~ 10mm bis 999 m	Beginning and ending ~ 10mm bis 999 m
Pull-off length	Adjustable	Adjustable
Speed	0.1 - 2.5 m/s, programmable	0.1 - 2.5 m/s, programmable
Acceleration	Adjustable	Adjustable
Cable guides	Fast and easy changeable cable guides	Fast and easy changeable cable guides
Cable tension / Torque	-	-
Power supply	3 x 400 VAC + N / 25 AT	3 x 400 VAC + N / 25 AT
Pneumatic	6 bar	6 bar
Weight	450 kg	530 kg
Dimension (L x W x H)	1350 x 900 x 1650 mm	1350 x 900 x 1650 mm

#### LOCATION SWITZERLAND

**Ramatech Systems AG** . Hohenrainstrasse 36 . CH - 6280 Hochdorf  
Phone: +41 41 914 26 26 . E-Mail: [info@ramatech.ch](mailto:info@ramatech.ch)

#### LOCATION GERMANY

**Ramatech Systems GmbH**. Messerschmittstraße 30 . D - 89231 Neu-Ulm  
Phone: +49 731 40 199 200 . E-Mail: [info@ramatech.de](mailto:info@ramatech.de)